Technical Datasheet



Chromapoxy - Balu Epoxy Aluminium Pigmented Paint

PRODUCT DESCRIPTION:

A two component Epoxy Bitumen based paint With aluminium pigmented.

USES:

For D.I.Pipes, Chemical Plants, Petrochemical Plants, Refineries, Pipelines, Fertilizers Plants, Pharmaceutical Units, Marine Installation Etc.

SURFACE PREPARATION:

Degrease and Blast clean to SA 21/2 grade minimum of Swedish specification SIS -05-5900-1967. Surface profile should not exceed 65 microns.

Surface should be clean dry free from oil grease, Salt and others contaminants before applying Chromapoxy BALU H.B.FN.Paint.

METHOD OF APPLICATION:

Stir base thoroughly and then mix four parts base and one part Hardener by volume to uniform consistency. Allow the mixture & stir again before application BRUSH/SPRAY (Airless spray recommended for uniform film stir again before application and wish film build)

NOTES OF AIRLESS SPRAY:

TIP RANGE 15-21 thou.
TOTAL OUTPUT FLUID PRESSURE:1500-2500 psi (106-176 kg/cm²)

MIXING RATIO:

Base : Accelerator = 4:1 By Volume

POT LIFE:

2-3 Hours

FINISH:

Smooth & Uniform Eggshell gloss.

RECOMMENDED DFT:

70 - 90 Microns (Minimum).

DRYING TIME:

Surface Dry: Within 2 Hours Handle able Dry: 18-24 hours Full Cure : 7 days

THEORETICAL SPREADING RATE:

6-4.6 M²/ Ltr /coat

Over coating Interval Min: 24 hours Max: 7days

FLASH POINT:

Above 20° C.

COLOUR:

Aluminium (Metallic Brown)

FINISH:

Smooth & Uniform Egg shell Gloss.

STORAGE LIFE:

Up to 9 months so long as the material is stored in a & cool place sealed container.

THINNER:

When necessary use NDC SPL. EPOXY Thinner for Chromapoxy BALU H.B.FN Paint.

PRECAUTIONS: Not to be applied when the temperature is above 500C and relative humidity rises 90%.

DISCLAIMER: The information given in this data sheet is best of our knowledge, observed while tested in ideal condition in our laboratory.

WORKS: POST & VILL & PO: BAMUNARI, NH -2, DELHI ROAD .DIST HOOGHLY, 712205,

WEST BENGAL. PHONE: 9830317320

OFFICE: JEEVAN NIWAS, 30A, BLOCK -R, NEW ALIPORE, 2ND FLOOR, FLAT A/5

KOLKATA: 700 053,

CONTACT: +91 9830848300 / 98308 49200 / 9674129944.